




# HEAT4ALL: MAIDSTONE CLASSIC/LEICESTER

Estimation of Building Heating Load & Heating Demand

23.07.2020

# GOAL & SCOPE

- Estimation of building heating demand and heating load for a residential building in Leicester (UK).
- Project: Maidstone Classic / Leicester



# DATA & CALCULATION ASSUMPTIONS

- Geometry
  - building plan (email 15.07.2020)
- Constructions & materials data
  - building plan & provided data (email 15.07.2020)
  - missing data estimated
- Thermal bridges
  - estimated
- Room air temperature:
  - $T_i = 20$  [°C]
- Air change rate
  - $ACH = 0,4$  [1/h]
- Internal gains
  - $q_i = 3,75$  [W/m<sup>2</sup>]


# CLIMATE DATA

- ASHRAE IWE2 weather file
  - Leicester/Peterborough/Cottesmore (UK)
  - Data from ASHRAE Fundamentals 2013

Design day data

Design data file:

	Winter	Summer	
Dry-bulb min	-4.3	14.1	°C
Dry-bulb max	0.3	26.0	°C
Wet-bulb max	-0.2	17.6	°C
Wind direction	270	210	°
Wind speed	3.1	5.6	m/s
Clear-sky tau_b	0.331	0.39	
optical depth tau_d	2.533	2.261	



# THERMAL CONDUCTANCE

Fixed infiltration airflow rate				19.261 l/s
Building envelope	Area [m <sup>2</sup> ]	U [W/(m <sup>2</sup> K)]	U*A [W/K]	% of total
<b>Walls above ground</b>	<b>66.19</b>	<b>0.31</b>	<b>20.77</b>	<b>28.73</b>
ExternalWall	66.19	0.31	20.77	28.73
<b>Walls below ground</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
<b>Roof</b>	<b>37.00</b>	<b>0.11</b>	<b>3.98</b>	<b>5.50</b>
Roof	37.00	0.11	3.98	5.50
<b>Floor towards ground</b>	<b>38.81</b>	<b>0.13</b>	<b>5.07</b>	<b>7.01</b>
Ground Floor	38.81	0.13	5.07	7.01
<b>Floor towards amb. air</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
<b>Windows</b>	<b>12.47</b>	<b>1.41</b>	<b>17.58</b>	<b>24.32</b>
Glazing	12.47	1.41	17.58	24.32
<b>Doors</b>	<b>1.69</b>	<b>1.98</b>	<b>3.34</b>	<b>4.62</b>
Entrance door1	1.69	1.98	3.34	4.62
<b>Thermal bridges</b>			<b>21.57</b>	<b>29.83</b>
<b>Total</b>	<b>156.16</b>	<b>0.46</b>	<b>72.31</b>	<b>100.00</b>

# HEATING LOAD



	Heating load [W]	Heat4All Infrared panel	Nominal output [W]
WC		SmartLine 175	175
Lounge		SmartLine 1000	1000
Kitchen		SmartLine 1000	1000
Bed1		SmartLine 520	520
En-Suit		SmartLine 320	320
Bed2		SmartLine 520	520
Bed3		SmartLine 320	320
Landing		SmartLine 175	175
Bath		SmartLine 320	320
Lobby		SmartLine 175	175
<b>Total</b>	<b>2 286</b>		<b>4 525</b>

# BUILDING HEATING DEMAND




	Envelope & Thermal bridges, kWh	Internal Walls and Masses, kWh	Window & Solar, kWh	Infiltration & Openings, kWh	Internal gains, kWh	Local heating units, kWh
During heating	-4 095	184	-360	-1 917	1 700	4 482
	£0.134 per kWh					£600.57
	£0.195 daily charge					£71.18
Electricity (for room heating)						£671.75

# NOTE



- The presented figures are based on a simplified non-standard estimate of the building heating demand and heating load. Deviating actual conditions (climate, user behavior, control settings, ventilation, building orientation, insulation,...) may cause significant deviation from the calculated results.





GENIO Bauphysik GmbH

Brauhausgasse 12  
9500 Villach  
[www.genio.gmbh](http://www.genio.gmbh)

Ing. Mag. Andreas Karitnig

+43 676 52 49 628  
[andreas.karitnig@genio.gmbh](mailto:andreas.karitnig@genio.gmbh)