HEAT4ALL ICONIC MIRROR PANEL (FRAMELESS)





PRODUCT SPECIFICATIONS

Surface: Rear panel: Field of application:

Surface temperature:

Voltage: Colour:

Safety specs:

Temperature protection:

Power supply:

INSTALLATION

wall mounting

ESG safety glass, smooth sheet steel, powder-coated direct heating approx. 90° C to 110° C 230 Volt, 50/60 Hz mirror

IP 45, protection class 1 1-2 sensors, depending on heater dimensions Type CEE 7/7 tilted, 8 mm flat; cable length: 1.9 m

Certificates:









No matter which room you choose for our Heat4All ICONIC Mirror Panels, be it your bathroom, dressing room or lobby area, they are sure to enthral. Their simple, elegant and practical design makes them the perfect heating solution for your living or office spaces.

MODEL	DIMENSIONS [mm]	NOMINAL OUTPUT [W]	WEIGHT [kg]	HEATABLE AREA [m²]
Heat4All ICONIC Mirror Panel 250	600 x 300 x 21	200	5.3	3-6
Heat4All ICONIC Mirror Panel 350	900 x 300 x 21	310	7.6	4-8
Heat4All ICONIC Mirror Panel 420	600 x 600 x 21	350	9.8	6-11
Heat4All ICONIC Mirror Panel 540	800 x 600 x 21	450	12.9	7-13
Heat4All ICONIC Mirror Panel 750	900 x 700 x 21	600	16.6	11-18
Heat4All ICONIC Mirror Panel 820	1700 x 400 x 21	710	18.1	12-20
Heat4All ICONIC Mirror Panel 870	1195 x 595 x 21	730	18.8	12-21
Heat4All ICONIC Mirror Panel 900	1000 x 800 x 21	780	20.5	13-22
Heat4All ICONIC Mirror Panel 1200	1200 x 800 x 21	1000	25.0	17-29
Heat4All ICONIC Mirror Panel 1250	1600 x 600 x 21	1000	25.0	18-30